

#### Description

The SM712 is designed for asymmetrical (12V to –7V) protection in multi-point data transmission application. The SM712 replace four discrete components by integrating two 12V and two 7V TVS diodes in a single package. The SM712 complies with the IEC 61000-4-2 (ESD) with  $\pm 30\text{kV}$  air and  $\pm 30\text{kV}$  contact discharge. It is assembled into a lead-free SOT-23 package. It is designed to protect components which are connected to data and transmission lines from voltage surges.

#### Features

- Ultra low leakage: nA level
- Operating voltage: 7V or 12V
- Low clamping voltage
- Complies with following standards:
  - IEC 61000-4-2 (ESD) immunity test
    - Air discharge:  $\pm 30\text{kV}$
    - Contact discharge:  $\pm 30\text{kV}$
  - IEC61000-4-5 (Lightning) 17A or 12A (8/20 $\mu\text{s}$ )
- RoHS Compliant

#### Mechanical Characteristics

- Package: SOT-23
- Lead Finish: Matte Tin
- Case Material: “Green” Molding Compound.
- Terminal Connections: See Diagram Below
- Marking Information: See Below

#### Applications



- Wireless System
- Networks
- Portable Instrumentation
- RS485 Ports

#### Ordering Information


Part Number	Packaging	Reel Size
SM712	3000/Tape & Reel	7 inch



SOT-23



Circuit diagram



712= Device code  
Marking (Top View)


## Absolute Maximum Ratings

Rating	Symbol	Value	Units
Peak Pulse Power (tp = 8/20μs)	P <sub>PK</sub>	300	W
Peak Pulse Current (tp = 8/20μs), Pin 1 or 2 to Pin 3	I <sub>PP</sub>	12	A
Peak Pulse Current (tp = 8/20μs), Pin 3 to Pin 1 or 2		17	
ESD per IEC 61000-4-2 (Contact)	V <sub>ESD</sub>	30	kV
ESD per IEC 61000-4-2 (Air)		30	
Lead Soldering Temperature	T <sub>L</sub>	260 (10 sec.)	°C
Operating Temperature	T <sub>J</sub>	-55 to +125	°C
Storage Temperature	T <sub>STG</sub>	-55 to +150	°C


## Electrical Characteristics (T=25°C unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Stand-Off Voltage	V <sub>RWM</sub>	Pin 1 or Pin 2 to 3			12	V
		Pin 3 to Pin 1 or 2			7	
Reverse Breakdown Voltage	V <sub>BR</sub>	I <sub>t</sub> = 1mA, Pin 1 or 2 to Pin 3	13.3			V
		I <sub>t</sub> = 1mA, Pin 3 and Pin 1 or 2	7.5			
Reverse Leakage Current	I <sub>R</sub>	V <sub>R</sub> = 12 V, Pin 1 or Pin 2 to 3			0.5	μA
		V <sub>R</sub> = 7 V, Pin 3 to Pin 1 or 2			0.5	
Clamping Voltage	V <sub>C</sub>	I <sub>PP</sub> = 5A, Pin 1 or 2 to Pin 3, tp = 8/20μs		18.5	20	V
		I <sub>PP</sub> = 5A, Pin 3 to Pin 1 or 2, tp = 8/20μs		12.5	14	
Clamping Voltage	V <sub>C</sub>	I <sub>PP</sub> = 12A, Pin 1 or 2 to Pin 3, tp = 8/20μs		22	26	V
		I <sub>PP</sub> = 17A, Pin 3 to Pin 1 or 2, tp = 8/20μs		17	19	
Junction Capacitance	C <sub>J</sub>	V <sub>R</sub> = 0V	Pin 1 or 2 to Pin 3	47		pF
			Pin 3 to Pin 1 or 2	47		
		V <sub>R</sub> = 12V	Pin 1 or 2 to Pin 3	22		
		V <sub>R</sub> = 7V	Pin 3 to Pin 1 or 2	35		


### Typical Performance Characteristics ( $T_A=25^\circ\text{C}$ unless otherwise Specified)




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time




Clamping Voltage vs. Peak Pulse Current



Power Derating Curve




8 X 20 $\mu\text{s}$  Pulse Waveform






ESD Clamping Voltage  
8 kV Contact per IEC61000-4-2


### SM712 on RS-485 Data Lines Application

EIA RS-485 specifies a  $\pm 7V$  ground difference between devices on the bus. This permits the bus voltage to range from +12V (5V + 7V) to -7V (0 - 7V). The SM712 is designed to protect two RS-485 data lines in extended common mode applications. The SM712 may be used to protect devices from transient voltages resulting from ESD, EFT, and lightning. The device is designed with asymmetrical operating voltages for optimum protection. The TVS diodes at pins 1 and 2 have a working voltage of 12volts. These pins are connected to the differential data line pairs. The TVS diodes at pin 3 have a working voltage of 7volts. Pin 3 is connected to ground. The internal TVS diodes of the SM712 will protect the transceiver input from positive transient voltage spikes greater than 12V and negative spikes greater than 7V.





Suggested Land Pattern



DIMENSIONS						
SYM	INCHES			MILLIMETERS		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.035	-	0.045	0.89	-	1.15
A1	0.000	-	0.004	0.01	-	0.10
A2	0.035	0.037	0.040	0.88	0.95	1.02
b	0.012	-	0.020	0.30	-	0.51
c	0.003	-	0.007	0.08	-	0.18
D	0.110	0.114	0.120	2.80	2.90	3.04
E	0.082	0.093	0.104	2.10	2.37	2.64
E1	0.047	0.051	0.055	1.20	1.30	1.40
e	0.075			1.90BSC		
e1	0.037			0.95BSC		
L	0.015	0.020	0.024	0.40	0.50	0.60
L1	0.022			0.55		
N	3			3		
θ	0°	-	8°	0°	-	8°
aaa	0.004			0.10		
bbb	0.008			0.20		

DIMENSIONS		
SYM	INCHES	MILLIMETERS
C	0.087	2.20
E	0.037	0.95
E1	0.075	1.90
G	0.031	0.80
X	0.039	1.00
Y	0.055	1.40
Z	0.141	3.60